

ATS

Pompa centrifuga a trattore con rotazione idraulica e tubo telescopico

Tractor driven centrifugal pump with hydraulic rotation and telescopic pipe



La pompa ATS, dotata di idraulica di tipo centrifugo, garantisce un'elevata modularità di pompaggio e una grande flessibilità di utilizzo anche con bassa sommergenza. Il tubo di mandata orientabile idraulicamente con tubo telescopico idraulico allungabile di 1,5 m garantisce la massima adattabilità adeguandosi con precisione alle svariate configurazioni di lavoro.

ATS pump, a centrifugal type of pump, grants high modularity when pumping and great flexibility of use even with low submergence. The hydraulically adjustable delivery pipe with a hydraulic telescopic pipe extensible of 1,5 meters grants the best adaptability, suiting with precision to the different working configurations.

CARATTERISTICHE | FEATURES

Modello Model	Giri/Min RPM	P [kW]	Q [l/s]	150	200	250	300	350	400	450	500
			Q [l/min]	9000	12000	15000	18000	21000	24000	27000	30000
			Q [mc/h]	540	720	900	1080	1260	1440	1620	1800
ATS 30	540	40	P [kW]	22	23	25	26				
			H [m]	7,5	6,4	5,3	3,6				
ATS 35	540	52	P [kW]	28	29	30	31	31	31,5	32	
			H [m]	7,6	7,1	6,4	5,6	4,7	3,6	2,3	
ATS 40	540	62	P [kW]	33,5	35	36	37	38	38,5	39	39
			H [m]	8,4	8	7,4	6,7	5,9	5	3,9	2,7

DIMENSIONI | DIMENSIONS

Modello Model	D [mm]	Telaio Frame [m]	H [m]	A [mm]	B [mm]	Peso Weight [kg]
ATS 30	300	3,5	1,9	3900	3375	570
		4	2,3	4400	3825	620
		5	3,1	5400	4825	670
ATS 35	350	3,5	2,1	4100	3410	580
		4	2,5	4600	3910	760
		5	3,2	5600	4910	820
ATS 40	400	3,5	2,1	4100	3470	760
		4	2,5	4600	3970	800
		5	3,2	5600	4970	880

